

COMPANY WITH QUALITY SYSTEM CERTIFIED BY DNV GL STEM CEA Sir Safety System S.p.A. Single-member company VAT Nr. IT 03359340548 export@sirsafety.com Wholly-owned subsidiary of Sir Holding Srl Viale Europa 74 www.sirsafety.com - 190 0001 -Via dei Fornaciai, 9 - Santa Maria degli Angeli 20090 Cusago Milano DNV.GI Tel. +39 02.90394575 (R.A.) 06081 Assisi - Perugia - Italy Tel.+39 075.8043737 (R.A.) - Fax +39 075.8048686 Fax +39 02.90394441 1000 021 Name: Camaro Sandal Code: 22017 **Total Plane Series** Description Sandal with 200 joule composite toecap and Zero Penetration midsole. Perforated suede leather and Mesh fabric upper. Eco-friendly leather overcap. Metal Free. REACTOR sole: Polyurethane/TPU sole. The open-cell polyurethane (PU) insole allows for a high shape memory effect and provides a cushioning effect. The TPU outsole provides flexibility, softness, as well as mechanical and chemical resistance. Especially after prolonged use, it enhances forefoot flexibility for a more natural motion, reducing fatigue. Anti-slip SRC standard. PLANTARE FODERA LAMINA Dual Dry PENETRAZIONE PENETRAZIONE DUAL FRESH Insoles in bi-component fabric with variable thickness and REACTOR shock-absorbing properties. They are made from special foams and particularly contact-friendly fabrics which prevent perspiration. DRY-PLUS polyester lining offering superb absorbing properties prevents feet overheating. Main features: - Conforming the German standard BGR 191, suitable for use of orthopaedic insoles. Curved sole to facilitate grip and walking - Innovative design - Ventilation holes for greater comfort - Total support of the outsole on the ground - Open angles to help releasing the impurities - Outsole with high memory performance - Outsole in TPU, resistant to oils and hydrocarbons - Grooves with open angles to discharge any accumulation - Horizontal grooves to improve flexibility and movements - Outsole in igh mechanical resistance and long-lasting TPU - Grooves pattern for better draining of liquids Anti-slip SRC standard The product is designed and manufactured to comply with the essential health and safety requirements of Directive 89/686/EEC, and to conform to the requirements of European standards EN ISO 20345. It is classified as PPE Cat. II. Colours Available Sizes Category II 39-47 Beige Quantity/Carton Important Information Recommended for The footwear should be stored in a cool dry place, Industrial plants, Construction and Road Work

 10
 Interform near sources and direct light.

 Make sure footwear is in good condition, before use. If the shoes are damaged, replace them.
 Sites, Edgisites and Handling.

 Dexterity
 EC Standards

 EN 20345
 Safety Class:S1P SRC

 BGR 191
 Safety Class:S1P SRC

Sites, Logistics and Handling.

far from heat sources and direct light.