



Sir Safety System S.p.A. Single-member company Wholly-owned subsidiary of Sir Holding Srl Via dei Fornaciai, 9 - Santa Maria degli Angeli 06081 Assisi - Perugia - Italy Tel.+39 075.8043737 (R.A.) - Fax +39 075.8048686

VAT Nr. IT 03359340548 Viale Europa 74 20090 Cusago Milano Tel. +39 02.90394575 (R.A.) Fax +39 02.90394441

export@sirsafety.com www.sirsafety.com

COMPANY WITH QUALITY SYSTEM CERTIFIED BY DNV GL



Code: 22034 **Total Plane Series** Name: Platinum Ankle High Shoe

Description

Dissipative footwear in class 2, ankle-high mode with 200 joule composite toecap and Zero Penetration composite midsole. Extra strong nubuck


REACTOR sole: Polyurethane/TPU sole. The open-cell polyurethane (PU) insole allows for a high shape memory effect and provides a cushioning effect. The TPU outsole provides flexibility, softness, as well as mechanical and chemical resistance. Especially after prolonged use, it enhances forefoot flexibility for a more natural motion, reducing fatigue. Anti-slip SRC standard.

EVA SOFT 3 MM INSOLES, with anti-weariness properties; interchangeable, ensuring continued hygiene and cleanliness. 3D-TEX LINING for foot ventilation, reducing perspiration.



- ESD
- Conforming the German standard BGR 191, suitable for use of orthopaedic insoles.
- Curved sole to facilitate grip and walking
- Innovative design
- Total support of the outsole on the ground
- Open angles to help releasing the impurities
- Outsole with high memory performance
- Outsole in TPU, resistant to oils and hydrocarbons
- Grooves with open angles to discharge any accumulation
- Horizontal grooves to improve flexibility and movements
- Outsole in igh mechanical resistance and long-lasting TPU
- Grooves pattern for better draining of liquids
- Anti-slip SRC standard

The product is designed and manufactured to comply with the essential health and safety requirements of Directive 89/686/EEC, and to conform to the requirements of European standards EN ISO 20345 and CEI EN 61340 - Dissipative Footwear Class 2. It is classified as PPE Cat. II.



(A)	SUOLA PU/TPU
ESD	REACTOR









Category	Colours	Available Sizes
II	Black	39-47
Quantity/Carton	Important Information	Recommended for
10	Keep the footwear dry and clean in an appropriate environment at ambient temperature. The wet footwear should never be placed in direct contact with a heat source after use, but shall be air-dried in a ventilated environment at ambient temperature. Make sure footwear is in good condition, before	Industrial plants, Construction and Road Work Sites, Logistics and Handling.
	use. If the shoes are damaged, replace them.	
Dexterity	EC Standards	Storage and cleaning



TECHNICAL SHEET

Sir Safety System S.p.A. Single-member company Wholly-owned subsidiary of Sir Holding Srl Via dei Fornaciai, 9 - Santa Maria degli Angeli

06081 Assisi - Perugia - Italy Tel.+39 075.8043737 (R.A.) - Fax +39 075.8048686 VAT Nr. IT 03359340548 Viale Europa 74 20090 Cusago Milano Tel. +39 02.90394575 (R.A.) Fax +39 02.90394441

export@sirsafety.com www.sirsafety.com

COMPANY WITH QUALITY SYSTEM CERTIFIED BY DNV GL = ISO 9001=



EN 20345

EN 20345 Safety Class:S3 SRC

EN 61340

EN 61340 Class:2

BGR 191

Clean the footwear with a soft brush and water. Do not use any substance such as alcohol, methyl ethyl ketone, thinners, gasoline, petrol or any other type of chemicals that could damage the materials, causing non-visible weakenings and compromise the original protective features.