



Sir Safety System S.p.A. Single-member company Wholly-owned subsidiary of Sir Holding Srl Via dei Fornaciai, 9 - Santa Maria degli Angeli 06081 Assisi - Perugia - Italy Tel.+39 075.8043737 (R.A.) - Fax +39 075.8048686 VAT Nr. IT 03359340548 Viale Europa 74 20090 Cusago Milano Tel. +39 02.90394575 (R.A.) Fax +39 02.90394441 export@sirsafety.com www.sirsafety.com

COMPANY WITH QUALITY SYSTEM CERTIFIED BY DNV GL = ISO 9001 =



Name: Firefighter Boot Code: 29106 Special Protection Series

Description

Waterproof safety boot designed for rescue and emergency teams; heat resistant vulcanised rubber upper, tractor tread sole with fire resistant, acid resistant, wear-and-tear, anti-slip, heat resistant and heat and cold insulating characteristics. With 200 joule toecap, steel midsole, ankle and heel reinforcement, heavy canvas cotton inner lining and pull-straps.

This footwear belongs to Special Protection Series, which guarantees high level of performance and quality; also due to the completeness of its range it ensures proper protection for any kind of danger, even the most extreme.

The product is designed and manufactured to comply with the essential health and safety requirements of Directive 89/686/EEC, and to conform to the requirements of European standards EN ISO 20345. It is classified as PPE Cat. III.



Black-Yellow	39-47
Important Information	Recommended for
The footwear should be stored in a cool dry place, far from heat sources and direct light. Make sure footwear is in good condition, before use. If the shoes are damaged, replace them.	Fire fighting teams, Firefighter, Forestry, Gardening and Maintenance of Green Spaces, Installers and Electricians.
EC Standards	Storage and cleaning
EN 20345	Clean the footwear with a soft brush and water.
Safety Class:S5 HI CI HRO SRA	
EN 15090	
Values:F2A HI3 P CI SRA	
	The footwear should be stored in a cool dry place, far from heat sources and direct light. Make sure footwear is in good condition, before use. If the shoes are damaged, replace them. EC Standards EN 20345 Safety Class:S5 HI CI HRO SRA EN 15090