



Sir Safety System S.p.A. Single-member company Wholly-owned subsidiary of Sir Holding Srl Via dei Fornaciai, 9 - Santa Maria degli Angeli 06081 Assisi - Perugia - Italy Tel.+39 075.8043737 (R.A.) - Fax +39 075.8048686

VAT Nr. IT 03359340548 Viale Europa 74 20090 Cusago Milano Tel. +39 02.90394575 (R.A.) Fax +39 02.90394441

export@sirsafety.com www.sirsafety.com

COMPANY WITH QUALITY SYSTEM CERTIFIED BY DNV GL



Name: Chemfor-TF Coverall Code: 30237TF Chemical Protection Type 4 - 5 - 6

## **Description**

Coverall with antistatic properties, in polypropylene coated with a hightenacity breathable microporous film; the specific material guarantees resistance against liquid splashes, including inorganic liquids, and dusts up to 0.6 micron. It features a zipper closure with flap and elastic hood, cuffs, waistband and ankles. It features a breathable rear part.

- High protection, resistant and breathable.
- Resistant to splashes, including inorganic liquids and dusts up to 0.6 micron
- Antistatic treatment.
- Hygienic, because it does not lose fibres.

The product is designed and manufactured according to the provisions of Council Directive 89/686/EEC, with harmonized standards EN 13982 TYPE 5. EN 13034 TYPE 6 and EN 1149.

It is classified as PPE Cat. III.



	Category	Colours	Available Sizes
	III	White	M-XXL
	Quantity/Carton	Important Information	Recommended for

25

Keep in a cool dry place, far from heat sources and direct light.

Make sure the garment is in good condition, undamaged and clean before use. Once you become aware of a damage, you should immediately replace it.

Cleaning, Construction, Industrial plants installation and maintenance, Waste and asbestos collection and disposal, Painting, Chemical and testing laboratories, Agribusiness industry, Shipbuilding, Reclamation and pest control.

Dexterity

**EC** Standards

EN 1149 CE



EN 13034 CE



Type:6

EN ISO 13982 CE

Type:5

Storage and cleaning

Keep in a cool dry place, far from heat sources and direct light.

Disposable equipment: no further inspection is necessary.

