

**Sir Safety System S.p.A. Single-member company**  
Wholly-owned subsidiary of Sir Holding Srl  
Via dei Fornaciai, 9 - Santa Maria degli Angeli  
06081 Assisi - Perugia - Italy  
Tel.+39 075.8043737 (R.A.) - Fax +39 075.8048686

VAT Nr. IT 03359340548  
Viale Europa 74  
20090 Cusago Milano  
Tel. +39 02.90394575 (R.A.)  
Fax +39 02.90394441

export@sirsafety.com  
www.sirsafety.com

COMPANY WITH  
QUALITY SYSTEM  
CERTIFIED BY DNV GL  
= ISO 9001 =



<b>Name: Metal Splash Trousers</b>	<b>Code: 33284</b>	<b>New Metal Splash</b>
------------------------------------	--------------------	-------------------------

### Description

Trousers in 54% Lenzing FR, 20% Wool, 20% Polyamide, 5% Aramid, 1% Antistatic Fibre, 330 g/m<sup>2</sup>, with zipper closure and concealed button, two side pockets and one rear pocket closed with flap and Velcro.

- Suitable for protecting the operator from short contact with the flame, in presence of low values of convective and radiant heat.
- It protects against welding and aluminium splashes.
- Its remarkable properties do not limit the softness and breathability.





The product is designed and manufactured to comply with the requirements of Directive 89/686/EEC.  
It is classified as PPE Cat. II.

Protection levels indicated refer to the combination jacket and trousers.



Category <b>III</b>	Colours Grey	Available Sizes 44-62
------------------------	-----------------	--------------------------

Quantity/Carton <b>5</b>	Important Information Keep in a cool dry place, far from heat sources and direct light. Make sure the garment is in good condition, undamaged and clean before use. Once you become aware of a damage, you should immediately replace it.	Recommended for Aluminium Industry, Foundries, Cement Industry.
-----------------------------	---	--

Dexterity	<p>EC Standards</p> <p>EN 1149 CE</p>  <p>EN 11611 CE</p> <p>Class:2;A1</p>  <p>EN 11612 CE</p>  <p>Limited Flame Spread:A1 Convective Heat:B1 Radiant Heat:C1 Molten Aluminium Splashes:D3 Molten Iron Splashes:E3 Contact Heat:F1</p>	<p>Storage and cleaning</p> <p>We recommend to follow the washing instructions.</p> 
-----------	--	--