

Sir Safety System S.p.A. Single-member company
Wholly-owned subsidiary of Sir Holding Srl
Via dei Fornaciai, 9 - Santa Maria degli Angeli
06081 Assisi - Perugia - Italy
Tel.+39 075.8043737 (R.A.) - Fax +39 075.8048686

VAT Nr. IT 03359340548
Viale Europa 74
20090 Cusago Milano
Tel. +39 02.90394575 (R.A.)
Fax +39 02.90394441

export@sirsafety.com
www.sirsafety.com

COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV GL
= ISO 9001 =



Name: Opera Quark Coverall	Code: 34165	Opera Quark Low Temperatures
-----------------------------------	--------------------	-------------------------------------

Description

Coverall specific for cold store operators, it is suitable for working in low temperatures down to -45°C. Outer fabric in 420D Oxford nylon and padding in Thinsulate 3M, 150 g/ m². Concealed zipper closure with flap and snap buttons, hood, cuffs adjustable with Velcro and inside cuffs in elastic knitted fabric; chest pocket with zipper, two side pockets with flaps and Velcro, elastic waistband, inner pocket with Velcro, reflective bands on the shoulders and under the knee, reflective piping on pockets' and shoulder pads' outlines.

- The Opera Quark series guarantees thermal protection down to -45°.
- The very thin thickness ensures lightness and softness allowing its use without limiting dynamism and comfort.

The product is designed and manufactured to comply with the essential health and safety requirements of Directive 89/686/EEC, and to conform to the requirements of European standards EN 342.
It is classified as PPE Cat. II.



Category III	Colours Blue	Available Sizes S-3XL
Quantity/Carton 500	Important Information Keep in a cool dry place, far from heat sources and direct light. Make sure the garment is in good condition, undamaged and clean before use. Once you become aware of a damage, you should immediately replace it.	Recommended for Agribusiness, Pharmaceutical industry, Logistics, Meat processing, Outdoor work.
Dexterity	EC Standards EN 342 CE 	Storage and cleaning We recommend to follow the washing instructions. 