



Sir Safety System S.p.A. Single-member company Wholly-owned subsidiary of Sir Holding Srl Via dei Fornaciai, 9 - Santa Maria degli Angeli 06081 Assisi - Perugia - Italy Tel.+39 075.8043737 (R.A.) - Fax +39 075.8048686 VAT Nr. IT 03359340548 Viale Europa 74 20090 Cusago Milano Tel. +39 02.90394575 (R.A.) Fax +39 02.90394441 export@sirsafety.com www.sirsafety.com

COMPANY WITH QUALITY SYSTEM CERTIFIED BY DNV GL = ISO 9001 =



Name: V-Guard Helmet Code: 38306 Head Protection - MSA

Description

Helmet made of UV stabilised high density polyethylene (HDPE), with Staz-On 4-point head harness and textile straps with ratchet wheel adjustment, for increased stability. Incorporated slots for hearing and face protection.

Weight: 350 g.

Approved EN 397 standard and responding to optional requirements:

- Very low temperature (-30°C)
- Electrical insulation (440V AĆ)
- Electrical insulation approval: EN 50365 electric shock up to 1000 V AC or 1500 V DC
- Antistatic approval: EN 13463-1 for the zone
- 1,2,21 and 22, Group IIA

The product is designed and manufactured to comply with the essential health and safety requirements of Directive 89/686/EEC, and to conform to the requirements of EN 397, EN 50365, EN 13463. It is classified as PPE Cat. III.



Colours	Available Sizes
Green	52-62
Important Information	Recommended for
Make sure the helmet is in good condition before use and its shell is not damaged: inspect for cracking, abrasions, change of colouring or dents. Once you become aware of a damage, you should immediately replace it.	Safety helmet suitable to protect the worker's head from objects falling from a height or accidental impacts in industrial plants.
EC Standards	Storage and cleaning
EN 397 CE EN 13463-1 CE Values:1, 2, 21, 22 Group:IIA EN 50365	Keep in a cool dry place, far from heat sources and direct light. Clean using only a neutral detergent and warm water. Do not use any solvents.
	Green Important Information Make sure the helmet is in good condition before use and its shell is not damaged: inspect for cracking, abrasions, change of colouring or dents. Once you become aware of a damage, you should immediately replace it. EC Standards EN 397 CE EN 13463-1 CE Values:1, 2, 21, 22 Group:IIA