

Sir Safety System S.p.A. Single-member company
Wholly-owned subsidiary of Sir Holding Srl
Via dei Fornaciai, 9 - Santa Maria degli Angeli
06081 Assisi - Perugia - Italy
Tel. +39 075.8043737 (R.A.) - Fax +39 075.8048686

VAT Nr. IT 03359340548
Viale Europa 74
20090 Cusago Milano
Tel. +39 02.90394575 (R.A.)
Fax +39 02.90394441

export@sirsafety.com
www.sirsafety.com

COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV GL
= ISO 9001 =



Name: V-Gard 500 Helmet	Code: 38311	Head Protection - MSA
--------------------------------	--------------------	------------------------------

Description

High quality helmet with ABS shell with Staz-On 4-point head harness and textile straps with ratchet wheel adjustment, for increased stability. Incorporated slots for hearing and face protection.
Weight: 400 g.
Size adjustment between 52-62 cm.

Approved EN 397 standard and responding to optional requirements:

- Very low temperature (-30°C)
- Lateral deformation (LD)
- Molten metal splashes (MM)
- Electrical insulation (440V AC)
- Electrical insulation approval: EN 50365 electric shock up to 1000 V AC or 1500 V DC
- Antistatic approval: EN 13463-1 for the zone 1,2,21 and 22, Group IIA.

The product is designed and manufactured to comply with the essential health and safety requirements of Directive 89/686/EEC, and to conform to the requirements of EN 397, EN 50365, EN 13463.
It is classified as PPE Cat. III.



Category III	Colours Yellow	Available Sizes 52-62
Quantity/Carton 20	Important Information Make sure the helmet is in good condition before use and its shell is not damaged: inspect for cracking, abrasions, change of colouring or dents. Once you become aware of a damage, you should immediately replace it.	Recommended for Safety helmet suitable to protect the worker's head from objects falling from a height or accidental impacts in industrial plants. The ABS shell ensures a high impact and chemical resistance, thus making the helmet a perfect protection device in chemical and petrochemical industry.
Dexterity	EC Standards EN 397 CE EN 13463-1 CE Values: 1, 2, 21, 22 Group: IIA EN 50365	Storage and cleaning Keep in a cool dry place, far from heat sources and direct light. Clean using only a neutral detergent and warm water. Do not use any solvents.