

**Sir Safety System S.p.A. Single-member company**  
Wholly-owned subsidiary of Sir Holding Srl  
Via dei Fornaciai, 9 - Santa Maria degli Angeli  
06081 Assisi - Perugia - Italy  
Tel.+39 075.8043737 (R.A.) - Fax +39 075.8048686

VAT Nr. IT 03359340548  
Viale Europa 74  
20090 Cusago Milano  
Tel. +39 02.90394575 (R.A.)  
Fax +39 02.90394441

export@sirsafety.com  
www.sirsafety.com

COMPANY WITH  
QUALITY SYSTEM  
CERTIFIED BY DNV GL  
= ISO 9001 =



<b>Name: High-Efficiency Disposable Respirator FFP3 NR D With Valve</b>	<b>Code: 45017</b>	<b>High Efficiency Disposable Respirators</b>
---	--------------------	---

High-efficiency disposable respirator. With exhalation valve. Suitable for use in polluted environments, as with aerosol and asbestos, with a high level of toxicity up to 50 times the TLV.  
Pack of 5 pieces.

- PVC outer structure gives a constant ergonomic shape.
- Completely sealed edge with polyurethane guarantees insulation from the outside.
- Carbon layer: it prevents irritation caused by low concentration of gases and acid that can penetrate together with dusts and aerosols.
- Great filtering capacity due to the broad cup surface.
- Microfibre material for reduced breathing resistance.
- Fully adjustable wide head straps for precise fit conforming to the face.
- Completely metal free, to avoid rusting.
- Preformed moulded structure, conforming to any face shape.



The product is designed and manufactured to comply with the essential health and safety requirements of Directive 89/686/EEC, and to conform to the requirements of EN 149.  
It is classified as PPE Cat. III.

FFP3 NR D  
FFP3: Nominal Protection Factor: 50  
Operational Protection Factor: 30  
NR: disposable  
D: The respirator has passed the dolomite clogging test.

Category <b>III</b>	Colours Light Blue	Available Sizes Unica
Quantity/Carton <b>60</b>	Important Information Make sure the product is in good condition and undamaged before use. Once you become aware of a damage, you should immediately replace it.	Recommended for Protects against aerosols and asbestos in concentrations up to 50 times the TLV. Suitable for grinding on fibreglass.
Dexterity	EC Standards EN 149:2001 + A1:2009 CE Class:FFP3 NR D	Storage and cleaning Keep in a cool dry place, far from heat sources.