

Sir Safety System S.p.A. Single-member company
Wholly-owned subsidiary of Sir Holding Srl
Via dei Fornaciai, 9 - Santa Maria degli Angeli
06081 Assisi - Perugia - Italy
Tel. +39 075.8043737 (R.A.) - Fax +39 075.8048686

VAT Nr. IT 03359340548
Viale Europa 74
20090 Cusago Milano
Tel. +39 02.90394575 (R.A.)
Fax +39 02.90394441

export@sirsafety.com
www.sirsafety.com

COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV GL
= ISO 9001 =



**Name: High-Efficiency Disposable Respirator
FFP3 NR D Carbon With Valve**

Code: 45018

High Efficiency Disposable Respirators

High-efficiency disposable respirator. With activated carbon layer. With exhalation valve. Suitable for use in polluted environments, as with aerosol and asbestos, with a high level of toxicity up to 50 times the TLV. Pak of 5 pieces.

- PVC outer structure gives a constant ergonomic shape.
- Completely sealed edge with polyurethane guarantees insulation from the outside.
- Carbon layer: it prevents irritation caused by low concentration of gases and acid that can penetrate together with dusts and aerosols.
- Great filtering capacity due to the broad cup surface.
- Microfibre material for reduced breathing resistance.
- Fully adjustable wide head straps for precise fit conforming to the face.
- Completely metal free, to avoid rusting.
- Preformed moulded structure, conforming to any face shape.

The product is designed and manufactured to comply with the essential health and safety requirements of Directive 89/686/EEC, and to conform to the requirements of EN 149.
It is classified as PPE Cat. III.

FFP3 NR D

FFP3: Nominal Protection Factor: 50

Operational Protection Factor: 30

NR: disposable.

D: The respirator has passed the dolomite clogging test.



Category III	Colours Light Blue	Available Sizes Unica
Quantity/Carton 60	Important Information Make sure the product is in good condition and undamaged before use. Once you become aware of a damage, you should immediately replace it.	Recommended for Protects against acid gases below TLV, along with contaminants with high toxicity up to 50 times the TLV, such as aerosols and asbestos. Suitable for welding activities and in low concentration levels of smells and acids below TLV, sanding and grinding on paint, plastic and stucco, cleaning with solvents and water sprays, on chimneys and incinerators, galvanizing processes.
Dexterity	EC Standards EN 149:2001 + A1:2009 CE Class:FFP3 NR D	Storage and cleaning Keep in a cool dry place, far from heat sources.