

TECHNICAL SHEET

Sir Safety System S.p.A. Single-member company Wholly-owned subsidiary of Sir Holding Srl Via dei Fornaciai, 9 - Santa Maria degli Angeli 06081 Assisi - Perugia - Italy Tel.+39 075.8043737 (R.A.) - Fax +39 075.8048686 VAT Nr. IT 03359340548 Viale Europa 74 20090 Cusago Milano Tel. +39 02.90394575 (R.A.) Fax +39 02.90394441 export@sirsafety.com www.sirsafety.com

COMPANY WITH QUALITY SYSTEM CERTIFIED BY DNV GL = ISO 9001 =



Name: High-Efficiency Disposable Respirator FFP3 NR With Valve

Code: 45170

High Efficency Disposable Respirators

High-efficiency disposable respirator. With exhalation valve. Suitable for use in polluted environments with a high level of toxicity up to 50 times the TLV.

Pack of 5 pieces.

The product is designed and manufactured to comply with the essential health and safety requirements of Directive 89/686/EEC, and to conform to the requirements of EN 149. It is classified as PPE Cat. III.

FFP3 NR D

FFP3: Nominal Protection Factor: 50 Operational Protection Factor: 30

NR: disposable

D: The respirator has passed the dolomite clogging test.



White	Unica
mportant Information	Recommended for
Make sure the product is in good condition and undamaged before use. Once you become aware of a damage, you should immediately replace it. Disposable equipment.	Protects against contaminants with high toxicity up to 50 times the TLV, such as asbestos, lead, chromium, nickel, uranium and other toxic elements. Suitable for sanding and grinding on fibreglass, demolition and cutting of asbestos, tunnel excavations.
EC Standards	Storage and cleaning
EN 149:2001 + A1:2009 CE	Keep in a cool dry place, far from heat sources.
Class:FFP3 NR	
ע ברוגיע ברוגיע	Make sure the product is in good condition and ndamaged before use. Once you become aware f a damage, you should immediately replace it. Disposable equipment. C Standards N 149:2001 + A1:2009 CE