

TECHNICAL SHEET

Name: High-Efficiency Disposable Respirator FFP2 NR Carbon With Valve	Code: 45181	High Efficiency Disposable Respirators
--	--------------------	---

High-efficiency disposable respirator, specific for welding work. Carbon layer with exhalation valve. Suitable for filtering vapours and acid fumes below the TLV. Suitable for use in polluted environments with a medium level of toxicity up to 12 times the TLV.
Pack of 5 pieces.

The product is designed and manufactured to comply with the essential health and safety requirements of Directive 89/686/EEC, and to conform to the requirements of EN 149.
It is classified as PPE Cat. III.

FFP2 NR D

FFP2: Nominal Protection Factor: 12

Operational Protection Factor: 10

NR: disposable.

D: The respirator has passed the dolomite clogging test.



Category III	Colours Grey	Available Sizes Unica
Quantity/Carton 60	Important Information Make sure the product is in good condition and undamaged before use. Once you become aware of a damage, you should immediately replace it.	Recommended for Protects against solid and liquid aerosols in concentrations up to 12 times the TLV. Suitable for brush, water based and epoxy painting, sanding and grinding on paint, stucco and plastic, cleaning with solvents and water sprays, in chimneys and incinerators, agriculture, feed and tobacco processing, foundries, metal degreasing, galvanizing, welding and oxy-acetylene cutting.
Dexterity	EC Standards EN 149:2001 + A1:2009 CE Class:FFP2 NR	Storage and cleaning Keep in a cool dry place, far from heat sources.