

**Sir Safety System S.p.A. Single-member company**  
Wholly-owned subsidiary of Sir Holding Srl  
Via dei Fornaciai, 9 - Santa Maria degli Angeli  
06081 Assisi - Perugia - Italy  
Tel.+39 075.8043737 (R.A.) - Fax +39 075.8048686

VAT Nr. IT 03359340548  
Viale Europa 74  
20090 Cusago Milano  
Tel. +39 02.90394575 (R.A.)  
Fax +39 02.90394441

[export@sirsafety.com](mailto:export@sirsafety.com)  
[www.sirsafety.com](http://www.sirsafety.com)

COMPANY WITH  
QUALITY SYSTEM  
CERTIFIED BY DNV GL  
= ISO 9001 =



<b>Name: Premium Respirator FFP1 NR D With Exhalation Valve</b>	<b>Code: 45186</b>	<b>Premium Disposable Respirators</b>
---	--------------------	---------------------------------------

### Description

Disposable Premium respirator with exhalation valve for low toxicity environments. Suitable up to 4 times the TLV.  
Pack of 10 pieces.

- Latex-free elastic straps, do not cause skin allergies.
- While not in use, thanks to its shape, the respirator remains in upright position, avoiding the accumulations of polluting agents in the inner part in contact with the face.
- Better face adaptability, due to its concave shape.
- Completely metal-free to prevent rusting.
- Greater protection from fine and toxic dusts, due to its new filter surface which passed the D test. This test is performed with Dolomite dusts and certifies a higher level of protection with added anti-clogging properties.

The product is designed and manufactured to comply with the essential health and safety requirements of Directive 89/686/EEC, and to conform to the requirements of EN 149.  
It is classified as PPE Cat. III.

FFP1 NR D

FFP1: Nominal Protection Factor: 4

Operational Protection Factor: 4

NR: disposable

D: The respirator has passed the dolomite clogging test.



Category <b>III</b>	Colours White	Available Sizes Unica
Quantity/Carton <b>120</b>	Important Information Make sure the product is in good condition and undamaged before use. Once you become aware of a damage, you should immediately replace it.	Recommended for Protects against solid and liquid aerosols in concentrations up to 4 times the TLV. Suitable for agriculture, threshing.
Dexterity	EC Standards EN 149:2001 + A1:2009 CE Class:FFP1 NR D	Storage and cleaning Keep in a cool dry place, far from heat sources.