

**Sir Safety System S.p.A. Single-member company**  
Wholly-owned subsidiary of Sir Holding Srl  
Via dei Fornaciai, 9 - Santa Maria degli Angeli  
06081 Assisi - Perugia - Italy  
Tel.+39 075.8043737 (R.A.) - Fax +39 075.8048686

VAT Nr. IT 03359340548  
Viale Europa 74  
20090 Cusago Milano  
Tel. +39 02.90394575 (R.A.)  
Fax +39 02.90394441

export@sirsafety.com  
www.sirsafety.com

COMPANY WITH  
QUALITY SYSTEM  
CERTIFIED BY DNV GL  
= ISO 9001 =



<b>Name: Premium Respirator FFP2 NR D Carbon With Valve</b>	<b>Code: 45192</b>	<b>Premium Disposable Respirators</b>
---	--------------------	---------------------------------------

Disposable Premium respirator with activated carbon layer and exhalation valve. Suitable for medium toxicity environments up to 12 times the TLV.  
Pack of 10 pieces.

- Latex-free elastic straps, do not cause skin allergies.
- While not in use, thanks to its shape, the respirator remains in upright position, avoiding the accumulations of polluting agents in the inner part in contact with the face.
- Better face adaptability, due to its concave shape.
- Completely metal-free to prevent rusting.
- Greater protection from fine and toxic dusts, due to its new filter surface which passed the D test. This test is performed with Dolomite dusts and certifies a higher level of protection with added anti-clogging properties.

The product is designed and manufactured to comply with the essential health and safety requirements of Directive 89/686/EEC, and to conform to the requirements of EN 149.  
It is classified as PPE Cat. III.

FFP2 NR D  
FFP2: Nominal Protection Factor: 12  
Operational Protection Factor: 10

NR: disposable  
D: The respirator has passed the dolomite clogging test.



Category <b>III</b>	Colours White	Available Sizes Unica
Quantity/Carton <b>120</b>	Important Information Make sure the product is in good condition and undamaged before use. Once you become aware of a damage, you should immediately replace it.	Recommended for Protects against solid and liquid aerosols in concentrations up to 12 times the TLV. Suitable for roller and epoxy painting, sanding and grinding on paint, cleaning and pest control in chimneys, agriculture, feed and tobacco processing, metal welding operations.
Dexterity	EC Standards EN 149:2001 + A1:2009 CE Class:FFP2 NR D	Storage and cleaning Keep in a cool dry place, far from heat sources.