

Sir Safety System S.p.A. Single-member company
Wholly-owned subsidiary of Sir Holding Srl
Via dei Fornaciai, 9 - Santa Maria degli Angeli
06081 Assisi - Perugia - Italy
Tel.+39 075.8043737 (R.A.) - Fax +39 075.8048686

VAT Nr. IT 03359340548
Viale Europa 74
20090 Cusago Milano
Tel. +39 02.90394575 (R.A.)
Fax +39 02.90394441

export@sirsafety.com
www.sirsafety.com

COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV GL
= ISO 9001 =



Name: FH1 Hood	Code: 45345	Powered Air-Purifying Tornado System - Scott
-----------------------	--------------------	---

Description

An ultra-light half hood for applications where impact protection is not required. The sealing frame of the FH1 mask is in Neoprene to allow a high level of protection without compromising the wearer's comfort. FH1 is manufactured from a durable PU-coated nylon material with a flexible visor in PETG.

Minimum airflow: 140 l/m
Assigned Protection Factor: 40
Nominal Protection Factor: 500
Actual hood weight: 150 g
Noise Level: <65 dB (A)
Hood Material: Polyurethane coated Nylon
Hose Material: Polyurethane
Visor Material: PETG
Eye Protection: EN 166 1F

The product is designed and manufactured to comply with the essential health and safety requirements of Directive 89/686/EEC, and to conform to the requirements of EN 12941.
It is classified as PPE Cat. III.



Category III	Colours Grey	Available Sizes
Quantity/Carton 1	Important Information The hood cannot be considered a chemical protective clothing. Make sure the item is in good condition, undamaged before use. Once you become aware of a damage, you should immediately replace it.	Recommended for
Dexterity	EC Standards EN 12941 CE	Storage and cleaning Keep in a cool dry place, far from heat sources.