

**Sir Safety System S.p.A. Single-member company**  
Wholly-owned subsidiary of Sir Holding Srl  
Via dei Fornaciai, 9 - Santa Maria degli Angeli  
06081 Assisi - Perugia - Italy  
Tel.+39 075.8043737 (R.A.) - Fax +39 075.8048686

VAT Nr. IT 03359340548  
Viale Europa 74  
20090 Cusago Milano  
Tel. +39 02.90394575 (R.A.)  
Fax +39 02.90394441

export@sirsafety.com  
www.sirsafety.com

COMPANY WITH  
QUALITY SYSTEM  
CERTIFIED BY DNV GL  
= ISO 9001 =



<b>Name: FH4 Hood</b>	<b>Code: 45348</b>	<b>Powered Air-Purifying Tornado System - Scott</b>
-----------------------	--------------------	---

### Description

Visor for welding protection. Entirely adjustable head protection incorporated. Supplied with one auto-darkening welding visor in accordance with EN 175.  
Suitable for various welding applications. The air is distributed directly into the breathing area and is exhaled from the mask's extremity.

Minimum airflow: 140 l/m  
Assigned Protection Factor: 20  
Nominal Protection Factor: 50  
Actual hood weight: 571 g without filter  
Hose Material: EPDM  
Visor Material: Polycarbonate  
Eye Protection: EN 175 B  
Filter: EN 379 CE

The product is designed and manufactured to comply with the essential health and safety requirements of Directive 89/686/EEC, and to conform to the requirements of EN 12941.  
It is classified as PPE Cat. III.



Category <b>III</b>	Colours Black	Available Sizes
Quantity/Carton <b>1</b>	Important Information The hood cannot be considered a chemical protective clothing. Make sure the item is in good condition, undamaged before use. Once you become aware of a damage, you should immediately replace it.	Recommended for
Dexterity	EC Standards EN 12941 CE	Storage and cleaning Keep in a cool dry place, far from heat sources.