

**Sir Safety System S.p.A. Single-member company**  
Wholly-owned subsidiary of Sir Holding Srl  
Via dei Fornaciai, 9 - Santa Maria degli Angeli  
06081 Assisi - Perugia - Italy  
Tel.+39 075.8043737 (R.A.) - Fax +39 075.8048686

VAT Nr. IT 03359340548  
Viale Europa 74  
20090 Cusago Milano  
Tel. +39 02.90394575 (R.A.)  
Fax +39 02.90394441

export@sirsafety.com  
www.sirsafety.com

COMPANY WITH  
QUALITY SYSTEM  
CERTIFIED BY DNV GL  
= ISO 9001 =



<b>Name: Bilsom Clarity Earmuffs</b>	<b>Code: 51153</b>	<b>Kombi Ear Muffs</b>
--------------------------------------	--------------------	------------------------

Helmet mounted earmuffs, available both with universal helmet attachment and with specific Rockman, Style 600, ABS 900 and Everest helmets attachment. High level of attenuation, among the highest of its class. It can be used in three positions: working, waiting and resting.

SNR 30 dB

Hertz frequency: H Attenuation = 28

Hertz frequency: M Attenuation = 28

Hertz frequency: L Attenuation = 24

Freq.(Hz)/Attenuation Med./Dev. standard/Value APV:63/15.4/3.5/11.9;

Freq.(Hz)/Attenuation Med./Dev. standard/Value APV:125/22.8/4.3/18.5;

Freq.(Hz)/Attenuation Med./Dev. standard/Value APV:250/27.4/3.2/24.2;

Freq.(Hz)/Attenuation Med./Dev. standard/Value APV:500/31.3/2.8/28.5;

Freq.(Hz)/Attenuation Med./Dev. standard/Value APV:1000/30.5/1.8/28.7;

Freq.(Hz)/Attenuation Med./Dev. standard/Value APV:2000/28.2/2.3/25.9;

Freq.(Hz)/Attenuation Med./Dev. standard/Value APV:4000/35.0/3.6/31.4;

Freq.(Hz)/Attenuation Med./Dev. standard/Value APV:8000/34.6/3.0/31.6;

The product is designed and manufactured to comply with the essential health and safety requirements of Directive 89/686/EEC, and to conform to the requirements of EN 352.

It is classified as PPE Cat. II.



Category <b>II</b>	Colours Light Blue	Available Sizes Unica
Quantity/Carton <b>20</b>	Important Information Make sure the device is in good condition before use. Once you become aware of a damage, you should immediately replace it.	Recommended for Suitable in steel industry, foundries and construction work sites.
Dexterity	EC Standards EN 352 CE	Storage and cleaning Keep in a cool dry place, far from heat sources. Clean with a damp cloth and soapy water. Do not use any solvents.