

TECHNICAL SHEET

Sir Safety System S.p.A. Single-member company Wholly-owned subsidiary of Sir Holding Srl Via dei Fornaciai, 9 - Santa Maria degli Angeli 06081 Assisi - Perugia - Italy Tel.+39 075.8043737 (R.A.) - Fax +39 075.8048686

VAT Nr. IT 03359340548 Viale Europa 74 20090 Cusago Milano Tel. +39 02.90394575 (R.A.) Fax +39 02.90394441

export@sirsafety.com	c
www.sirsafety.com	CE

Sokoi Harnesses

COMPANY WITH QUALITY SYSTEM CERTIFIED BY DNV GL = ISO 9001 =



Name: Sokoi 1 Harness

Code: 55311

Description

The harness is made in polyester and it features:

- 1 dorsal "D" attachment for the fall arrest system.
- Adjustable chest belt and leg loops.
- Chest strap holding shoulder straps.

- Wider comfortable straps for extended time use.

Sokoi harnesses are in polyester, which has lower elongation properties than other materials. The harness does not stretch dangerously when subject to a fall, therefore, the worker does not risk slipping out of the harness.

Sokoi harnesses may be equipped, upon request, with a Tell-Tale fall indicator, positioned, through the seams, on the back of the shoulder; it detaches itself in the event of a fall. The harness must be immediately replaced after a fall.

Technical Specifications:

- Dorsal "D" Attachment for the fall arrest system.

- "A" or "A/2" label: shows the attachment points of the fall arrest system.

- Labels: all the harnesses labels and markings are in an inner strong

polyethylene wrapping to prevent the marking from fading.

- Sliders: the ends of the shoulders straps are locked by plastic lips.

- All the texile loops are covered with a fabric reinforcement.

The product is designed and manufactured to comply with the essential health and safety requirements of Directive 89/686/EEC, and to conform to the requirements of EN 361. It is classified as PPE Cat. III.



Category	Colours	Available Sizes
III	Yellow - Blue	Unica
Quantity/Carton	Important Information	Recommended for
1	Read carefully the user sheet included. Make sure the item is in good condition, undamaged before use. Once you become aware of a damage, you should immediately replace it.	Suitable for work at height.
Dexterity	EC Standards	Storage and cleaning
	EN 361 CE	Keep in a dry place, far from heat sources.