

Sir Safety System S.p.A. Single-member company Wholly-owned subsidiary of Sir Holding Srl Via dei Fornaciai, 9 - Santa Maria degli Angeli 06081 Assisi - Perugia - Italy Tel.+39 075.8043737 (R.A.) - Fax +39 075.8048686

VAT Nr. IT 03359340548 Viale Europa 74 20090 Cusago Milano Tel. +39 02.90394575 (R.A.) Fax +39 02.90394441

TECHNICAL SHEET

export@sirsafety.com www.sirsafety.com

Sokoi Harnesses

COMPANY WITH QUALITY SYSTEM CERTIFIED BY DNV GL = ISO 9001 =



Name: Sokoi 3 Harness

Code: 55313

Description

The harness is made in polyester and it features:

- 2 chest "D" attachments and 1 dorsal "D"
- attachment for the fall arrest system.

- Adjustable shoulder straps and leg loops.

- Sliding frontal plate for strap adjustment.
- Totally adjustable harness.

- Sitting waistbelt designed for maximum comfort of the worker.

Sokoi harnesses are in polyester, which has lower elongation properties than other materials. The harness does not stretch dangerously when subject to a fall, therefore, the worker does not risk slipping out of the harness.

Sokoi harnesses may be equipped, upon request, with a Tell-Tale fall indicator, positioned, through the seams, on the back of the shoulder; it detaches itself in the event of a fall. The harness must be immediately replaced after a fall.

Technical Specifications:

- Dorsal "D" Attachment for the fall arrest system.

- "A" or "A/2" label: shows the attachment points of the fall arrest system.

- Labels: all the harnesses labels and markings are in an inner strong polyethylene wrapping to prevent the marking from fading.

- Sliders: the ends of the shoulders straps are locked by plastic lips.
- All the texile loops are covered with a fabric reinforcement.

The product is designed and manufactured to comply with the essential health and safety requirements of Directive 89/686/EEC, and to conform to the requirements of EN 361. It is classified as PPE Cat. III.

Category	Colours	Available Sizes
III	Yellow - Blue	Unica
Quantity/Carton	Important Information	Recommended for
1	Read carefully the user sheet included. Make sure the item is in good condition, undamaged before use. Once you become aware of a damage, you should immediately replace it.	Suitable for work at height.
Dexterity	EC Standards EN 361 CE	Storage and cleaning Keep in a dry place, far from heat sources.

