

**Sir Safety System S.p.A. Single-member company**  
Wholly-owned subsidiary of Sir Holding Srl  
Via dei Fornaciari, 9 - Santa Maria degli Angeli  
06081 Assisi - Perugia - Italy  
Tel.+39 075.8043737 (R.A.) - Fax +39 075.8048686

VAT Nr. IT 03359340548  
Viale Europa 74  
20090 Cusago Milano  
Tel. +39 02.90394575 (R.A.)  
Fax +39 02.90394441

export@sirsafety.com  
www.sirsafety.com

COMPANY WITH  
QUALITY SYSTEM  
CERTIFIED BY DNV GL  
= ISO 9001 =



<b>Name: Stratos 2 Harness</b>	<b>Code: 55323</b>	<b>Stratos Harnesses</b>
--------------------------------	--------------------	--------------------------

### Description

Fall arrest harness in polyester, 44 mm wide, with breaking force 23 Kn.  
It features:

- 1 dorsal "D" attachment. 2 textile chest loops.
- 2 lateral "D" rings on waist, for work positioning.
- Fully adjustable and padded shoulder.
- Straps and legs loops. Padded and adjustable waistbelt with quick-attach buckle.
- Work positioning sitting belt especially designed for greater comfort. The shoulder straps and leg loops are provided with automatic quick-attach buckles. 2 back loops for tool-carrying. Textile loops inserted on shoulder straps to set single lanyards.
- Sitting belt specially designed for prolonged comfort. Padded straps for better shock absorption and a greater user comfort.
- Weight: 2,20 kg.

### Technical Specifications:

- Elastic Loops: specially designed to retain the excess strap while adjusting.
- Automatic Buckles: 1 stainless steel.
- Lanyard Keepers: on both sides for attaching lanyards safely.
- Shoulders straps and leg loops: fully padded, with quick attach buckles. The particular padding ensures better shock absorption and air circulations.
- "I D" Plate: back plate enclosing the two crossing dorsal straps, keeping the D-ring in place, even after a fall.
- Work positioning belt: padded, with lateral D-rings for extra confort while working. Features a back handle for attaching extra accessories.
- Combination Sliders: easy to adjust, even with one hand.

Stitching thread: High tenacity polyamide.

Static Force: 15 kN o 1.530 Kg per 3 minutes per every attaching element.

Weight: 2,20 kg

The product is designed and manufactured to comply with the essential health and safety requirements of Directive 89/686/EEC, and to conform to the requirements of EN 361, EN 358.  
It is classified as PPE Cat. III.



Category <b>III</b>	Colours Green	Available Sizes Unica
Quantity/Carton <b>1</b>	Important Information Read carefully the user sheet included. Make sure the item is in good condition, undamaged before use. Once you become aware of a damage, you should immediately replace it.	Recommended for Suitable for work at height.
Dexterity	EC Standards EN 358 CE  EN 361 CE	Storage and cleaning Keep in a dry place, far from heat sources.