

Sir Safety System S.p.A. Single-member company
Wholly-owned subsidiary of Sir Holding Srl
Via dei Fornaciai, 9 - Santa Maria degli Angeli
06081 Assisi - Perugia - Italy
Tel. +39 075.8043737 (R.A.) - Fax +39 075.8048686

VAT Nr. IT 03359340548
Viale Europa 74
20090 Cusago Milano
Tel. +39 02.90394575 (R.A.)
Fax +39 02.90394441

export@sirsafety.com
www.sirsafety.com

COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV GL
= ISO 9001 =



TECHNICAL SHEET

Name: Tripod Structure

Code: 55329

Work Positioning Systems

Description

Telescopic, tubular aluminium structure with 3 ground standing points. Essential for descent operations into wells, mine shafts or holes otherwise inaccessible. Features a 20 m winch for lifting or lowering a person and relative equipment up to a weight of 500 Kg. The wire-ending is fitted with a karabiner which shall be connected to harnesses with dorsal and sternal attachment points. The Tripod is ideal for the maintenance and inspections of wells, sewers, lifts, etc.; moreover it allows for the rescue of workers who have fainted or who are injured.

Cable diameter: 4,5 mm
Static strength: > 12 kN for 3 min.
Maximum height: 2.15 m
Minimum height: 1,15 m

The product is designed and manufactured to comply with the essential health and safety requirements of Directive 89/686/EEC, and to conform to the requirements of EN 795.
It is classified as PPE Cat. III.



Category

III

Colours

Aluminium - Red

Available Sizes

Unica

Quantity/Carton

1

Important Information

Read carefully the user sheet included.
Make sure the item is in good condition, undamaged before use. Once you become aware of a damage, you should immediately replace it.

Recommended for

Essential for descent operations into wells or holes which would be otherwise inaccessible.

Dexterity

EC Standards

EN 795 CE

Storage and cleaning

Keep in a dry place, far from heat sources.