

TECHNICAL SHEET

Sir Safety System S.p.A. Single-member company Wholly-owned subsidiary of Sir Holding Srl Via dei Fornaciai, 9 - Santa Maria degli Angeli 06081 Assisi - Perugia - Italy Tel.+39 075.8043737 (R.A.) - Fax +39 075.8048686 VAT Nr. IT 03359340548 Viale Europa 74 20090 Cusago Milano Tel. +39 02.90394575 (R.A.) Fax +39 02.90394441 export@sirsafety.com www.sirsafety.com

COMPANY WITH QUALITY SYSTEM CERTIFIED BY DNV GL = ISO 9001=



Name: Milan 2.0 Power Rescue Device Code: 55600 Rescue Devices - Skylotec

Description

Rescue device equipped with descending and lifting function. Electrically operated if combined with the special drill. It works with rope of only 9 mm diameter - available in various lengths depending on the requirements. Max. number of operators: 2. Abseiling speed: 0.9 m/s. Maximum abseiling height: 250 m.

The product is designed and manufactured to comply with the essential health and safety requirements of Directive 89/686/EEC, and to conform to the requirements of EN 341 and EN 1496. It is classified as PPE Cat. III.



Category	Colours	Available Sizes
III	Black	Unica
Quantity/Carton	Important Information	Recommended for
1	The storage and operating status of the fall protection PPE must be checked periodically, at leat once a year.	
Dexterity	EC Standards	Storage and cleaning
	EN 341 CE EN 1496	Maintenance must be carried out by qualified personnel. After fall, the PPE must be checked by specialist personnel who will certify the fitness for use or the need for it to be replaced.