

Wholly-owned subsidiary of Sir Holding Srl Via dei Fornaciai, 9 - Santa Maria degli Angeli 06081 Assisi - Perugia - Italy Tel.+39 075.8043737 (R.A.) - Fax +39 075.8048686

COMPANY WITH QUALITY SYSTEM CERTIFIED BY DNV GL NSTEM CER Sir Safety System S.p.A. Single-member company VAT Nr. IT 03359340548 export@sirsafety.com Viale Europa 74 www.sirsafety.com 20090 Cusago Milano DNV.GI Tel. +39 02.90394575 (R.A.) Fax +39 02.90394441 1000 021 Code: 81603X3 Gas Detectors - BW Name: Gas Alert Microclip XL 1 Gas (LEL) Description Gas Alert Microclip X3 1 Gas, it detects 1 gas (Fuels). It features a protection level equivalent to IP68, with water- resistance up to 45 minutes at a depth of 1.2 m. Battery running time up to 18 hour, single button operating. Reliable battery performance, Reflex ™ technology to ensure the reactivity of the sensor, compact, lightweight and easy to use, green IntelliFlash ™ flashing light for an immediate visual confirmation. Five-year life expectancy — plus a three-year warranty. An all-new oxygen sensor that operates consistently for five years - with no replacement costs for the life of the detector. It features: - Functioning guaranteed for at least a 12 hour shift, down to -20 ° C. - Rechargeable lithium polymer long-lasting battery, tested to withstand extreme conditions. - Ergonomic, lightweight and easy to wear. - Gas concentration constantly displayed on LCD screen. - Alarm lightbars, with a wide viewing angle. - The IP68 protection ensures maximum protection against dust and water: up to 45 minutes at a depth of 1.2 m. - Easy functioning, tamper-proof with a single button and intuitive LCD icons. - IntelliFlash <sup>™</sup> light shows whether the detector has been subjected to impact test and is working properly. - Full function self-test of sensor, battery status, circuit integrity and audio/visual alarms. Dimensions: 11,3 x 6,0 x 3,2 cm; Weight: 179 g Temperature: from -20° C up to 50° C. Humidity: from 0 up to 95% RH (without moisture) Acoustic (95dB), visual and vibrating alarm. Low, high, TWA, STEL, OL (Over Limit). Battery operating time:18 hours; It recharges in less than 6 hours User options: Reliability beep; Set STEL interval; On/off sensor; Alarms with manual reset; Safe display; stealth mode; calibration block; Auto-zero at startup; Automatic O2 calibration at startup; Set bump test interval; Mandatory impact test to overcoming of expiring date; IntelliFlash ™ range; Fuels measurement (% LEL or% by volume of methane); User-settable calibration gas level; Calibration obliged to overcome the maturity; Acceptance low alarm; Multilingual support; Setting custom boot message. -IP68 Nominal values: fino a 45 minuti a 1.2 m Certifications: Class I, Div. 1, Group A, B, C, D ATEX: II 1 G Ex ia IIC T4 Ga IECEx: Ex ia IIC T4 Ga **European Compliance** 

KTL

Category Colours Available Sizes Ш Yellow Quantity/Carton Recommended for Important Information



Sir Safety System S.p.A. Single-member company Wholly-owned subsidiary of Sir Holding Srl Via dei Fornaciai, 9 - Santa Maria degli Angeli 06081 Assisi - Perugia - Italy Tel.+39 075.8043737 (R.A.) - Fax +39 075.8048686		VAT Nr. IT 03359340548 Viale Europa 74 20090 Cusago Milano Tel. +39 02.90394575 (R.A.) Fax +39 02.90394441	export@sirsafety.com www.sirsafety.com	COMPANY WITH QUALITY SYSTEM CERTIFIED BY DNV GL = ISO 9001 =	
	Make sure the product is undamaged and clean b become aware of a dam immediately replace it.		n before use. Once you amage, you should	Suitable to detect the presence of Fuels.	
	Dexterity	EC Standards EN 60079-0 EN 60079-11		Storage and cleaning Keep in a cool dry place, far from heat sources.	



Sir Safety System S.p.A. Single-member company Wholly-owned subsidiary of Sir Holding Srl Via dei Fornaciai, 9 - Santa Maria degli Angeli 06081 Assisi - Perugia - Italy Tel.+39 075.8043737 (R.A.) - Fax +39 075.8048686

VAT Nr. IT 03359340548 Viale Europa 74 20090 Cusago Milano Tel. +39 02.90394575 (R.A.) Fax +39 02.90394441 TECHNICAL SHEET

export@sirsafety.com cu www.sirsafety.com cerr

COMPANY WITH QUALITY SYSTEM CERTIFIED BY DNV GL = |SO 9001 =

